

1880

1000428805

Home >> Catalog >> Products >> Wheel loaders >> 18 Series >> 1880



1880

Material number 1000428805

Articulated Hoftrac/farm loader with 61 hp and 3.4 t operating weight

Product details

Drive system

- •Hydrostatic all-wheel drive system, travel direction can be chosen via joystick
- •Service brake: Hydrostatic drive system acting on all 4 wheels (wear-free)
- •Central service and parking brake in the drive train acts on all 4 wheels
- •100% differential lock, electro-hydraulic connectable on front and rear axle

Hydraulics

- •3rd front control circuit, electrically proportionally controlled in parallel via joystick, hydraulic oil cooler
- •Floating position for lift and tipping cylinders

Cabin

- •Operator's canopy with roll-over protective structure / FOPS-tested restraint system, including rear window, driver's
- •Fully suspended comfort seat with safety belt, weight, back and height adjustment
- •Joystick with motion direction control and integrated touch button for differential lock
- •Work lights 2 in front and 2 in rear, operating hour meter, fuel gauge
- •Adjustable steering column

Other

- •Toolbox in the vehicle rear
- •Bucket state display; self-rescue coupling

Errors and omissions are reserved. The information in this data sheet is based on present knowledge. However, this neither guarantees specific product features nor establishes a legally valid contractual relationship.

Comes with
Machine
Errors and omissions are reserved. The information in this data sheet is based on present knowledge. However, this neither guarantees specific product features nor establishes a legally valid

contractual relationship.

Technical specifications

1880

ENGINE	Metric
Battery capacity (nom. value)	95 Ah
Power rating max.	45,0 kW, 45,0 kW
Engine operating mode	four-stroke
Cooling	Water-cooling, Water-cooling
Exhaust-gas limit	V
Alternator	null, null
Engine speed (Power max.)	2.800 1/min
Engine type	Diesel engine
Cylinder	4, 4
Engine Manufacturer	Perkins, Perkins
Cylinder capacity	2.216 cm3, 2.200 cm3
Kraftstofftyp	Diesel EN 590
Engine Designation	404J-E22TA
MECHANICAL - OUTPUT DETAILS	Metric
Travel speed (Option)	30,0 km/h
Travel speed	20,0 km/h
HYDRAULIC	Metric
Flow rate max.	56 l/min
Operating pressure hydraulics	250,0 bar
MECHANICAL DETAILS	Metric
Operating weight	3.400,0 kg
Length	4.715 mm
Tipping load	2.032 kg

Errors and omissions are reserved. The information in this data sheet is based on present knowledge. However, this neither guarantees specific product features nor establishes a legally valid contractual relationship.

Height	2.346 mm
Width	1.214 mm
CHASSIS	Metric
Turning radius	3.171 mm

Please Note

This product availability can vary from country to country. It is possible that information / products may not be available in your country. More detailed information on engine power can be found in the operator's manual; the started power may vary due to specific operating conditions. Subject to alterations and errors expected. Applicable also to illustrations.

Copyright © 2024 Wacker Neuson SE