



**WACKER
NEUSON**
all it takes!

PT3A

5000009101

[Home](#) >> [Catalog](#) >> [Products](#) >> [Pumps](#) >> [Trash Pumps](#) >> [Self Priming Trash Pumps](#) >> **PT3A**



PT3A

Material number 5000009101

Gasoline powered self-priming trash pump, Honda engine

Product details

- Hardened ductile iron impeller and volute offer long life and easy maintenance
- High strength, lightweight aluminum housing
- Easy access and large fill and drain plugs
- Radial flow design produces high volume and head

Comes with

- Centrifugal Trash Pump
- Strainer
- T-bolt clamp
- BSP nipple fittings
- Operator's manual

Technical specifications

PT3A

OPERATING FLUIDS	Metric
Tank capacity	5,30 l
ENGINE	Metric
Power rating max.	5,9 kW
Engine operating mode	four-stroke
Engine speed 1	3.500 1/min
Cooling	air cooling
Consumption at Speed 1	2,2 L/Std
Operating Engine speed	3.500 1/min
Engine speed (Power max.)	3.600 1/min
Run Time at Speed 1	2,5 std
Engine type	Gasoline engine
Cylinder	1
Engine Manufacturer	Honda
Standard (Operating power)	SAE J1349
Cylinder capacity	270 cm3
Kraftstofftyp	Gasoline
MECHANICAL - OUTPUT DETAILS	Metric
Flow rate max.	1.350 l/min
Suction head max.	7,6 m
Solid diameter max.	38,0 mm
Delivery height max.	29,0 m
SHIPPING AND STORAGE	Metric
Width for shipping	521 mm

Shipping weight	75,00 kg
Height for shipping	610 mm
Length for shipping	689 mm

ENVIRONMENT DATA	Metric
Sound power LWA, guaranteed	102,0 dB(A)

MECHANICAL DETAILS	Metric
Operating weight	68,0 kg
Length	673 mm
Intake-/Pressure socket-dia.	75 mm
Height	569 mm
Width	505 mm

Please Note

This product availability can vary from country to country. It is possible that information / products may not be available in your country. More detailed information on engine power can be found in the operator's manual; the started power may vary due to specific operating conditions. Subject to alterations and errors expected. Applicable also to illustrations.

Copyright © 2024 Wacker Neuson SE